

Technical Data Sheet

Filtration Products



Attributes & Properties [◇]

Name:	RP1350 / 612L INTREPID® Filtration Media
Color:	White
Basis Weight:	3.25 ounces per square yard Range 3.05 to 3.45 ounces per square yard (110 grams / square meter) Range 103 to 117 grams per square meter
Efficiency:	56.0 % Minimum 47.5% TSI Model 8130 automated filter tester with 0.1 µm count median diameter NaCl particles at 85 liters per minute.
Air Permeability:	225 cubic feet of air/minute per square foot of media Range 180 to 270 cfm (1.14 cubic meter of air / second per square meter of media) Range 0.91 to 1.37 meter ³ / sec per meter ² of media Textest FX 3300 Labotester III
MD Gurley Stiffness: Roll Average	410 milligrams Lower Limit 230 milligrams
Thickness:	0.039 inches Range 0.033to 0.045 inches (0.99 millimeters) Range 0.84 to 1.14 millimeters Testing load of 0.025 psi (172.4 Pascals)
Inside Core: Diameter	6.75 inches (171 millimeters)

[◇] Unless otherwise noted, the material described in this document is available for commercial sale and sold with a limited warranty. Kimberly-Clark Corporation and/or Kimberly-Clark Worldwide retains all intellectual property rights to this material, including trademarks and trade names. If the material described is defined as developmental, the material properties are estimates only and are not warranted by Kimberly-Clark Corporation.

Technical Data Sheet Filtration Products



1400 Holcomb Bridge Road
Roswell, Georgia 30076-2199
Phone: 770-587-8000
www.kcprofessional.com



Technical Data Sheet

Filtration Products



Attributes & Properties [◇]

RP1350 / 612L INTREPID® Filtration Media page 2

=====

Roll Length: 1,500 linear yards
(1,372 linear meters)

Roll Diameter: 42 inches
(1016 millimeters)
estimated

Slit Width Tolerance: +1/8, -1/8 inch (+3 mm, -3 mm)
Slit width tolerance measured at the outside of the roll, under tension.

Air Entering Side: The air entering side of the filter media faces the core.

Packaging: Cardboard headers, full stretch wrap coverage, multiple slit rolls of the same width may be packaged together into a Powerpack

Roll Labeling Information:

Slit Roll Label

Slit roll number
Product name and description
Production date
Basis weight
Slit width
Roll length
Roll weight
Country of origin

Powerpack Label

Powerpack number
Product name and description
Production date
Basis weight
Roll weight
Slit width
Total square yards in the powerpack
Total linear yards in the powerpack
Country of origin

Production Reference:
Revision: NJZ 01/31/2015

GNW ETQ SPEC-08454

[◇] Unless otherwise noted, the material described in this document is available for commercial sale and sold with a limited warranty. Kimberly-Clark Corporation and/or Kimberly-Clark Worldwide retains all intellectual property rights to this material, including trademarks and trade names. If the material described is defined as developmental, the material properties are estimates only and are not warranted by Kimberly-Clark Corporation.